


DATA BASED ON :
 SUCTION DRY AIR 68 °F - 20 °C
 SUCTION PRESSURE 14.7 PSI
 SERVICE LIQUID WATER
 SERVICE LIQUID TEMPERATURE 59 °F - 15 °C
 TOLERANCE 10%

PERFORMANCE DATA
 TRAVAINI
 LOW PRESSURE
 LIQUID RING COMPRESSORS

PUMP MODEL	RPM	5 P.S.I.G.			10 P.S.I.G.			15 P.S.I.G.			20 P.S.I.G.			25 P.S.I.G.			28 P.S.I.G.		
		CAPACITY CFM	MOTOR HP	S.LIQUID G.P.M	CAPACITY CFM	MOTOR HP	S.LIQUID G.P.M	CAPACITY CFM	MOTOR HP	S.LIQUID G.P.M	CAPACITY CFM	MOTOR HP	S.LIQUID G.P.M	CAPACITY CFM	MOTOR HP	S.LIQUID G.P.M	CAPACITY CFM	MOTOR HP	S.LIQUID G.P.M
TRV 40-110	1750	68	5.6	2.8	68	6.3	3.1	67	7.1	3.6	65	8	4.2	62	9.0	5.0	59	9.5	5.4
TRV 40-150	1750	97	7.8	2.8	95	9.0	3	90	10.1	3.6	88	11.4	4.2	80	12.5	5	77	13.0	5.4
TRV 50-220	1750	141	11.0	3	140	13	3.5	139	18	4.7	135	18	8.0	125	19.5	8.8	113	20.0	7.9
TRV 65-300	1750	207	12.5	4.5	207	16	6	203	19.7	8	197	22	11	180	25.0	14	166	26.0	15.5
TRV 65-450	1750	295	16	5	293	22	7	288	27	10	273	32	12	230	36.0	15.5	200	38.0	18.5

****The above models can be used as compressors or vacuum pumps. Please see Page No. column to locate corresponding data sheets.
 For compressor performance curves refer to next page.**



Premier Fluid Systems
 Canadian Home of Travaini Pumps

4161 Morris Dr. - Unit 5 * Burlington * Ontario * L7L 5L5 * Website: www.pfspumps.com
 Tel: 1-800-461-2611 or 905-637-2611 * Fax: 905-333-4722 * email: info@pfspumps.com

DATE : APRIL 2012

N°.: 11.1